Lista sa podacima o proizvodima

Specifikacije



Acti9 iIL indikatorska lampica - crvena - 110-230 VAC

A9E18320

Osnovne informacije

range of product	Acti 9
Ime proizvoda	Acti 9 iIL
Tip proizvoda ili komponente	Modularna signalna lampica
Kratko ime uređaja	iIL
[us] nazivni napon	110...230 V AC pri 50/60 Hz 110...130 V DC

Dopunske informacije

indicator light	1 LED crvena, 100000 sati 0,3 W)
Način montiranja	Fiksno
Nosači za montažu	Simetričnu DIN šinu
Razvodni blok češljaste sabirnice	Gornji: ProDis
9 mm redovi	2
Visina	82 mm
Širina	18 mm
Dubina	69,5 mm
Boja	Bela (RAL 9003)
Pomoćni priključni blok	Tunel klema 1 kabl(ovi) kruti 0,5 mm² Tunel klema 2 kabl(ovi) kruti 2,5 mm² Tunel klema 1 kabl(ovi) fleksibilni 0,5 mm² Tunel klema 2 kabl(ovi) fleksibilni 2,5 mm² Tunel klema 2 kabl(ovi) fleksibilni sa kablovskim završetkom 2,5 mm²
Dužina ogoljenog dela žice	9 mm
Moment pritezanja	1 N.m

Okruženje

Standardi	IEC 60947-5-1
Ip stepen zaštite	IP2 IPxx B
Stepen zaprljanosti	3
Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C
Temperatura okoline za rad uređaja	-35…70 °C
Temperatura okoline za skladištenje	-40…80 °C

Sve cene koje su navedene u ovom cenovniku su informativne i neobavezujuće, bez PDV-a, isključivo u odnosu na ovlašćene distributere kompanije Schneider Electric. Svi prikazi, opisi i tehničke specifikacije i podaci u ovom cenovniku su podložni promenama od strane kompanije Schneider Electric bez prethodne najave.

Odricanje odgovornosti: Ova dokumentacija nije namenjena kao zamena i ne treba je koristiti za utvrđivanje podobnosti ili pouzdanosti ovih proizvoda za određene namene

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9,000 cm
Package 1 Width	2,000 cm
Package 1 Length	7,000 cm
Package 1 Weight	38,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	7,900 cm
Package 2 Width	9,900 cm
Package 2 Length	23,400 cm
Package 2 Weight	516,000 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30,000 cm
Package 3 Width	30,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	5,120 kg

Ugovorna garancija

Garancija (u mesecima)	18

Environmental Data

Schneider Electric namerava da postigne nulti status do 2050. godine kroz partnerstva sa lancem snabdevanja, materijale sa manjim uticajem i cirkularnost kroz našu tekuću kampanju "Use Better, Use Longer, Use Again" za produženje životnog veka proizvoda i reciklaže.

Objašnjeni Environmental Data >

Kako procenjujemo održivost proizvoda >

Ekološki otisak

Ukupan životni vek ugljeničnog otiska	**3 kg CO2 eq.**
Ugljenični otisak faze proizvodnje [A1–A3]	**0.9 kg CO2 eq.**
Ugljenični otisak faze distribucije [A4]	**0 kg CO2 eq.**
Ugljenični otisak faze instalacije [A5]	**0 kg CO2 eq.**
Ugljenični otisak faze korišćenja [B2, B3, B4, B6]	**2 kg CO2 eq.**
Ugljenični otisak faze kraja životnog ciklusa [C1–C4]	**0.2 kg CO2 eq.**
Izjava o zaštiti okoliša	**Profil ekološke prihvatljivosti proizvoda**

Use Better

Materijali i pakovanje

Pakovanje sa recikliranim kartonom	**Ne**
Pakovanje bez plastike	**Da**
SCIP broj	**6763a476-30bc-4d05-a4bb-93f8d65c3771**
Direktiva RoHS	**Usklađenost Sa Oslobađanjem**
Uredba REACh	**Referenca sadrži SVHC iznad propisanog praga**
OECD PFAS Regulation	**Ne OECD PFAS hemikalije prisutne**
POP Directive	**Nema POPs**
Status bez halogena	**Proizvod sa plastičnim delovima bez halogena**
Bez PVC-a	**Da**

Use Again

Prepakovanje i prefabrikovanje

Potencijal za recikliranje, u %	**23**
Profil cirkularnosti	**Nema potrebe za namenskim operacijama recikliranja**
Povraćaj	**No**
WEEE oznaka	**Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.**